

## Cube SUV Hybrid Pro glossy´n´flashred



|            |                                                           |
|------------|-----------------------------------------------------------|
| Modelljahr | 2015                                                      |
| Material   | Aluminium Superlite, ARG 27.5er, double butted, disc only |
| Gabel      | SR Suntour XCR Air LO-R 29, 100mm                         |
| Bremse     | Shimano A-M506, Hydr. Disc Brake (180/160)                |
| Farben     | glossy´n´flashred                                         |
| UVP:       | 2.299,00 EUR                                              |

|                |                                                                                   |            |                                |
|----------------|-----------------------------------------------------------------------------------|------------|--------------------------------|
| Felgen         | CUBE ZX24                                                                         | Pedale     | CUBE Aluminium MTB             |
| Sattel         | SDG Rock City                                                                     | Kurbelsatz | FSA Metropolis Urban AL-8, 15T |
| Sattelstütze   | CUBE Performance Post, 30,9mm                                                     | Akku       | Bosch Power Pack 400           |
| Sattelklemmung | RFR Varioclose 34.9mm                                                             |            |                                |
| Lenker         | CUBE Rise Trail Bar, 660mm                                                        |            |                                |
| Vorbau         | CUBE Performance Pro, 6°                                                          |            |                                |
| Griffe         | CUBE Natural Fit Race                                                             |            |                                |
| Steuersatz     | CUBE 1.5E ZS, top zero-stack 1 1/8" (OD 44mm), bottom zero-stack 1 1/2" (OD 56mm) |            |                                |