

## Stevens Primera SX Disc Lady



|            |                                            |
|------------|--------------------------------------------|
| Modelljahr | 2016                                       |
| Material   | Aluminium 6061 TB                          |
| Gabel      | SR Suntour NCX-D LO, 63mm, Aluminiumschaft |
| Bremse     | Tektro Vela, 180/160mm 6-Bolt              |
| Schaltung  | Shimano Deore Shadow RD-M610-SGS           |
| Größen     | 46, 50, 54cm                               |
| Farben     | Anthracite                                 |

|              |                                                 |             |                                                 |
|--------------|-------------------------------------------------|-------------|-------------------------------------------------|
| Schalthebel  | Shimano Deore SL-M610                           | Bremshebel  | Tektro Vela                                     |
| Umwerfer     | Shimano Deore FD-T610-L3                        | Beleuchtung | B+M IQ2 Eyc T Senso+ 50 Lux   Toplight View+    |
| Reifen       | Continental Contact 2 Extralight 42-622, Reflex | Pedale      | City Superlite Cartridge                        |
| Felgen       | Ryde Taurus 2000, 19C                           | Kurbelsatz  | Shimano FC-T521, 48-36-26Z.                     |
| Naben        | Shimano DH-3D32   FH-M475                       | Kette       | Shimano CN-HG54                                 |
| Sattel       | Selle Royal Freccia Lady                        | Extras      | Racktime E-1-Träger   integr. Pletscher-Ständer |
| Sattelstütze | Oxygen Driver                                   |             |                                                 |
| Lenker       | Oxygen Driver 15°, 630mm                        |             |                                                 |
| Vorbau       | Oxygen Driver 31.8mm, 17°                       |             |                                                 |
| Steuersatz   | STEVENS AH 1 1/8", ZS44/28.6   ZS44/30          |             |                                                 |