

# RadSPORT Gerbracht e.K.

Flechtendorfer Str. 7, 34497 Korbach

Telefon: 05631 7376  
Telefax: 05631 60613

E-Mail: info@gerbracht.de  
Internet: www.gerbracht.de



## Specialized Fatboy Expert

Big Wheels Big Fun

Der Fun Faktor eines Fat Bikes plus die gewohnt hohe Performance von Specialized. Der Fatboy kombiniert einen leichten Rahmen und eine spezielle Gabel mit 4.6" Specialized Ground Control Reifen für einfaches Handling bei extremsten Bedingungen.

ehem. UVP:

2.599,00\*

nur:

**1.999,00\***

|              |  |            |   |
|--------------|--|------------|---|
| Rahmen       | New Specialized M4 Premium Aluminum, Fat Bike Geometry, fully butted w/ smooth         | Felgen     | Specialized Fatboy SL, alloy disc, single wall, 90mm wide, sleeve joint, hookless   |
| Gabel        | FACT carbon full monocoque, 5.0" tire clearance, 135mm spacing                         | Reifen     | Specialized Ground Control, 26x4.6", Kevlar bead, 120TPI                            |
| Schaltung    | SRAM X0, Type 2, 10-speed  | Naben      | Specialized MTB disc, alloy, Hi Lo flange, sealed bearings, 135mm wide, alloy axle, |
| Schalthebel  | SRAM S-Series, Grip Shift twist shifter, 10-speed                                      | Pedale     | Specialized Bennies, 6061 alloy body, sealed cartridge bearings, removal 4.5mm      |
| Umwerfer     | SRAM X7, low direct mount  | Kurbelsatz | Custom e.thirteen, 2 piece, PF30, 100mm spindle, 170mm/175mm length                 |
| Bremse       | Shimano Deore, BR-505, hydraulic disc  |            |   |
| Bremshebel   | Shimano Deore, hydraulic lever, w/ reach adj.  |            |   |
| Sattel       | Body Geometry Henge SL, hollow Cr-Mo rails, lite PU foam, 143mm                        |            |   |
| Sattelstütze | Specialized alloy, 2-bolt, micro-adjust, 30.9mm, 350mm/400mm                           |            |   |
| Lenker       | Specialized mini riser bar, 6061 double-butted alloy, 660/700mm wide,                  |            |   |
| Vorbau       | Specialized 3D forged 6061 alloy, 4-bolt clamp, 6-degree rise, 60mm/70mm length,       |            |   |
| Steuersatz   | 1-1/8" upper and 1-1/2" lower FSA, Campy style w/ integrated cartridge bearings, 3.8mm |            |   |