

EPIC COMP CARBON 29 WORLD CUP



CARB/RKT RED/LT BLU



CARB/WHT

Das Epic Comp Carbon 29 World Cup mit seinem leichten und steifen Rahmen aus FACT 9m Karbon und 95mm Federweg ist ein konsequentes XC- und Marathonbike mit herausragenden Handling-Eigenschaften. "World Cup" bedeutet eine noch direktere XC-Geometrie und 1x11 Antrieb für superschnelle Schaltvorgänge. Der Specialized/FOX Brain-Dämpfer und die Rock Shox Reba RL Federgabel sorgen für hohe Kontrolle auf anspruchsvollen XC-Strecken. Die SWAT-Integration eines Mini-Tools im Oberrohr ist ein äußerst cleveres Feature. Der SRAM GX 1x11 Antrieb mit 30t Kettenblatt und 10-42 Kassette ist auch für steilere Anstiege geeignet. Shimanos hydraulische Scheibenbremsen stehen für optimale Funktion und hohe Zuverlässigkeit. Das Epic World Cup in einem Satz: Schneller kannst du auf XC Strecken und Marathons nicht sein!

- Leichter FSR-Rahmen aus hochfestem FACT 9m Karbon, Hinterbau aus M5 Aluminium, spezielle 29er World-Cup Geometrie für spritziges Handling und optimale Effizienz; interne Zugverlegung, 95mm Federweg.
- Der Specialized/FOX Mini Brain-Dämpfer mit Autosag-Funktion für leichte Anpassbarkeit auf dein Fahrergewicht unterscheidet automatisch zwischen glatten und unebenen Untergründen und verbindet so Effizienz und Kontrolle; 95mm Federweg; Du fährst, das Brain denkt mit.
- Rock Shox Reba RL mit 100mm Federweg und 15mm-Steckachse für hohe Kontrolle; einstellbare Druck- und Zugstufe.

2016 EPIC 29 CARBON WC				
SIZE	S	M	L	XL
Stack (mm)	583	597	611	630
Reichweite (Reach) (mm)	398	423	446	465
Steuerrohrlänge (mm)	90	105	120	140
Steuerrohrwinkel (deg)	71	71	71	71
Tretlagerhöhe (mm)	332	332	332	332
Tretlagerabsenkung (mm)	40	40	40	40
Nachlauf (mm)	82	82	82	82
Gabellänge (mm)	499	499	499	499
Fork Rake/Offset (mm)	46	46	46	46
Mitte Tretlager - Mitte Vorderachse (mm)	633	661	691	717
Kettenstreben (mm) (mm)	439	439	439	439
Radstand (mm)	1073	1103	1131	1157
Oberrohrlänge (horizontal) (mm)	562	592	618	643
Bike-Überstandshöhe (mm)	770	774	780	793
Sitzrohrlänge (mm)	400	434	470	520
Sitzrohrwinkel (deg)	74	74	74	74
Lenkerbreite (mm)	720	720	720	720
Vorbaulänge (mm)	70	90	100	110
Kurbellänge (mm)	170	175	175	175
Sattelstützen-Länge (mm)	350	400	400	400

SPECS	Technische Änderungen vorbehalten.
RAHMEN	FACT 9m carbon, World Cup XC 29 Geometry, M5 rear triangle, carbon PF30 BB, carbon headset cups, 142mm dropouts, internal cable routing, PM 160 rear brake, SWAT tool cradle
DÄMPFER	FOX/Specialized remote Mini Brain, AUTOSAG, Brain Fade adjust I-Valve, 200x48mm
GABEL	RockShox Reba RL 29, Solo Air spring, 100mm travel, compression adjust, rebound adjust, tapered alloy crown/steerer, 46mm offset, 15mm Maxle Stealth thru-axle
STEUERSATZ	1-1/8" upper, 1-1/2" lower, threadless, Campy style, cartridge bearings
VORBAU	Specialized Stout XC, 3D forged alloy, 4-bolt, 6-degree rise, anti-corrosion hardware
LENKER	Specialized, butted 6000 alloy, 8-degree backsweep, 6-degree upsweep, 10mm rise, 720mm, 31.8mm
LENKERGRIFFE	Specialized Sip Grip, light lock-on, half-waffle, S/M: regular thickness, L/XL: XL thickness
VORDERRADBREMSE	Shimano Deore BR-M506, hydraulic disc, dual piston, resin pads
HINTERRADBREMSE	Shimano Deore BR-M506, hydraulic disc, dual piston, resin pads
BREMSEBEL	Shimano BR-M615, hydraulic
SCHALTWERK	SRAM GX X Horizon, 11-speed, alloy cage
SCHALTHEBEL	SRAM GX, 11-speed, trigger
KASSETTE	SRAM XG-1150, 11-speed, 10-42t
KETTE	KMC X11L, 11-speed, w/ reusable MissingLink
KURBELGARNITUR	SRAM GX-1000, 11-speed, PF30, 30T X-Sync ring, 94mm BCD spider
INNENLAGER	SRAM, PF30, OS press-in bearings, sealed cartridge
PEDALE	Nylon, CEN std., w/ toe clips
FELGEN	Roval 29, alloy, 21mm inner width, 32h
VORDERRADNABE	Specialized, Hi Lo disc, sealed cartridge bearings, 15mm thru-axle, 32h
HINTERRADNABE	Specialized, Hi Lo disc, 4x sealed cartridge bearings, 12mm thru-axle, 32h
SPEICHEN	DT Swiss Industry, stainless
VORDERREIFEN	S-Works Fast Trak, 120TPI, 2Bliss Ready, folding bead, 29x2.0"
HINTERREIFEN	Specialized Fast Trak Control, 60TPI, 2Bliss Ready, folding bead, 29x2.0"
SCHLÄUCHE	Standard, Presta valve
SATTEL	Body Geometry Phenom Comp, hollow Cr-Mo rails, 143mm
SATTELSTÜTZE	Specialized, alloy, single bolt, 30.9mm
SATTELSTÜTZKLEMME	Alloy, 31.6mm

PART NO.	DESCRIPTION	COLOR	SIZE
90316-5402	EPIC COMP CARBON 29 WORLD CUP CARB/RKT RED/LT BLU		S
90316-5403			M
90316-5404			L
90316-5405			XL
90316-5502	EPIC COMP CARBON 29 WORLD CUP CARB/WHT		S
90316-5503			M
90316-5504			L
90316-5505			XL