

HOTROCK 24 21-SPEED BOYS



BLK/WHT/CYAN



ORG/BLK/WHT

Ein robuster A1 Premium Aluminiumrahmen, eine Federgabel mit 50mm Federweg und die große Antriebsbandbreite mit 21 Gängen machen dieses Hotrock 24 für alle größeren Kids zum perfekten Bike für die ersten Trail-Abenteuer.

- Rahmen aus A1 Premium Aluminium für viel Kontrolle durch niedrige Überstandshöhe.
- Die leichten 32-Loch-Aluminiumfelgen verkraften auch harte Belastungen.
- Die zuverlässigen V-Bremsen sorgen in Verbindung mit einstellbaren Bremshebeln für sicheres Verzögern und Anhalten.

2016 HOTROCK 24	
SIZE	BOYS
Stack (mm)	495
Reichweite (Reach) (mm)	354
Steuerrohrlänge (mm)	130
Steuerrohrwinkel (deg)	69
Tretlagerhöhe (mm)	221.5
Tretlagerabsenkung (mm)	35
Nachlauf (mm)	56
Gabellänge (mm)	376
Fork Rake/Offset (mm)	40
Mitte Tretlager - Mitte Vorderachse (mm)	574
Kettenstreben (mm) (mm)	410
Radstand (mm)	982
Oberrohrlänge (horizontal) (mm)	505
Bike-Überstandshöhe (mm)	615
Sitzrohrlänge (mm)	312
Sitzrohrwinkel (deg)	73
Lenkerbreite (mm)	0
Vorbaulänge (mm)	0
Kurbellänge (mm)	0
Sattelstützen-Länge (mm)	0

SPECS	Technische Änderungen vorbehalten.
RAHMEN	Specialized A1 Premium Aluminum, formed top tube/down tube, forged dropouts, replaceable alloy derailleur hanger
GABEL	SR Suntour XCT-JR, coil/MCU spring, 50mm travel, preload adjust, 1-1/8" steerer, alloy lowers, Hi-Ten 25.4mm stanchions, direct press type dust seal, disc and V-brake mount
STEUERSATZ	Ahead, 1/8" sealed cartridge bearings
VORBAU	Ahead, forged alloy, 4-bolt, 20-degree rise
LENKER	Specialized, flat bar, alloy, 6-degree backsweep, 25.4mm
LENKERGRIFFE	Specialized, Kraton, Revo type
VORDERRADBREMSE	V-brake, alloy, linear pull
HINTERRADBREMSE	V-brake, alloy, linear pull
BREMSHEBEL	Tektro, alloy, linear pull compatible
UMWERFER	Shimano Tourney
SCHALTWERK	Shimano TX-35, MegaRange, 7-speed
SCHALTHEBEL	Shimano Revo-Shift, 7-speed
KASSETTE	Shimano, 7-speed freewheel, 14-28t
KETTE	KMC HV500, 1/2"x3/32"
KURBELGARNITUR	Forged alloy arms, w/ chainguard
KETTENBLÄTTER	42/34/24T
INNENLAGER	68x119mm, semi-cartridge, w/ bolts
PEDALE	Nylon, BMX style, loose ball bearings, 9/16", w/ reflectors
FELGEN	24", alloy single wall, pin joint, 32h
VORDERRADNABE	Alloy, 3/8" axle, loose ball bearings, dual lock nuts, 17mm contact side, nutted, 32h
HINTERRADNABE	Alloy, loose ball, dual lock nuts, 17mm contact side, steel nutted axle, 32h
SPEICHEN	Stainless, 14g
VORDERREIFEN	Specialized Roller, 30TPI, wire bead, 24x2.125"
HINTERREIFEN	Specialized Roller, 30TPI, wire bead, 24x2.125"
SCHLÄUCHE	Standard, Schrader valve
SATTEL	Specialized Kids, 7mm rails, w/ bumper
SATTELSTÜTZE	Alloy, single bolt, 27.2mm
SATTELSTÜTZKLEMME	Alloy, 31.8mm

PART NO.	DESCRIPTION	COLOR	SIZE
B4E0-7511	HOTROCK 24 21-SPEED BOYS	BLK/WHT/CYAN	24
B4E0-7811	HOTROCK 24 21-SPEED BOYS	ORG/BLK/WHT	24