



BLK/MON GRN/HYP

Das Camber Grom mit 110mm Federweg am Heck ist für junge Mountainbiker gemacht, die ihre Skills ausbauen und viel Spaß am MTB-Sport haben wollen. Die 24"-Laufräder sorgen für eine niedrige Überstandshöhe, was maximale Sicherheit und Kontrolle schafft. Da sich auch 26"-Laufräder verbauen lassen, können Heranwachsende noch länger Freude an ihrem Camber Grom haben.

- Rahmen aus M5 Aluminium mit Grom-Geometrie, 135mm Einbaubreite hinten für hohe Laufrad-Kompatibilität und SRAM DMD Umwerfer-Adapter; niedriger Überstand, 110mm Federweg, optional 26"-Laufräder verwendbar
- Der FOX FLOAT Performance DPS Dämpfer wird über das steife "Concentric Linkage" linear angelenkt, was ein sensibles Ansprechverhalten und optimal nutzbare 110mm Federweg ergibt; AUTOSAG-Funktion für leichte Abstimmung auf das Fahrergewicht.
- Die RockShox Recon Gold mit 110mm Federweg gibt jungen Bikern volle Kontrolle.

2016 CAMBER GROM	
SIZE	GROM
Stack (mm)	547
Reichweite (Reach) (mm)	388
Steuerrohrlänge (mm)	110
Steuerrohrwinkel (deg)	68,5
Tretlagerhöhe (mm)	291
Tretlagerabsenkung (mm)	30
Nachlauf (mm)	83
Gabellänge (mm)	480
Fork Rake/Offset (mm)	40
Mitte Tretlager - Mitte Vorderachse (mm)	643
Kettenstreben (mm) (mm)	420
Radstand (mm)	1066
Oberrohrlänge (horizontal) (mm)	540
Bike-Überstandshöhe (mm)	621
Sitzrohrlänge (mm)	394
Sitzrohrwinkel (deg)	74,5
Lenkerbreite (mm)	700
Vorbaulänge (mm)	60
Kurbellänge (mm)	155
Sattelstützen-Länge (mm)	350

SPECS	Technische Änderungen vorbehalten.
RAHMEN	M5 alloy, 26 geometry, threaded BB, tapered head tube, 135mm rear spacing, DMD mount, SRAM FD adaptor, disc mount, 110mm travel
DÄMPFER	FOX FLOAT Performance DPS, 3-position compression adjust, rebound adjust, 6.5x1.358"
GABEL	RockShox Recon Gold, Solo Air spring, 110mm travel, rebound adjust, TurnKey lockout, tapered alloy steerer, 42mm offset, 9mm QR dropout
STEUERSATZ	1-1/8" upper, 1-1/2" lower, threadless, Campy style, cartridge bearings
VORBAU	Specialized Trail, forged alloy, 4-bolt, 8-degree rise
LENKER	Specialized, 7050 alloy, 8-backsweep, 6-upsweep, 10mm rise, 750mm, 31.8mm
LENKERGRIFFE	Specialized Sip Grip, lock-on, half-waffle, regular thickness
VORDERRADBREMSE	Tektro Gemini Comp, hydraulic disc, resin/metallic pads
HINTERRADBREMSE	Tektro Gemini Comp, hydraulic disc, resin/metallic pads
BREMSHEBEL	Tektro Gemini Comp, hydraulic, reach adjust
SCHALTWERK	SRAM X7 Type 2, 10-speed, mid cage
SCHALTHEBEL	SRAM X5, 10-speed, aluminum trigger, w/ Matchmaker clamp
KASSETTE	SRAM PG-1020, 10-speed, 11-36t
KETTE	SRAM PC-1031, 10-speed, w/ PowerLink, nickel finish
KURBELGARNITUR	SRAM GX-1000, GXP spindle, 155mm arms, 32T X-Sync ring, 104mm BCD spider,
INNENLAGER	SRAM GXP XR, 73mm
PEDALE	Nylon, 9/16", loose ball bearings, w/ reflectors
FELGEN	Alex, 24", 32h
VORDERRADNABE	Specialized, Hi Lo disc, OS28 end caps, sealed cartridge bearings, QR, 32h
HINTERRADNABE	Specialized, Hi Lo disc, 4x-sealed cartridge bearings, 12mm thru-axle, 142+ spacing, 32h
SPEICHEN	Stainless, 14g
VORDERREIFEN	Maxxis Snyper, 60TPI, wire bead, 24x2.0"
HINTERREIFEN	Maxxis Snyper, 60TPI, wire bead, 24x2.0"
SCHLÄUCHE	Standard, Presta valve
SATTEL	Specialized youth, steel rails
SATTELSTÜTZE	Specialized, alloy, single bolt, 30.9mm
SATTELSTÜTZKLEMME	Specialized, 7050 alloy, single bolt, 34.9mm

PART NO.	DESCRIPTION	COLOR	SIZE
93216-7602	CAMBER GROM	BLK/MON GRN/HYP	S