



CL GRY/MX ORG/SLT

Unser Enduro Expert EVO macht gekonnt den Spagat zwischen Freerider und DH-Bike. Der superstabile Rahmen aus M5 Aluminium besitzt überlegene Handlingeigenschaften dank spezieller 650b-Geometrie: superkurze Kettenstreben, lange Front, niedriges Tretlager, flacher Steuerwinkel. Mit sattten 180mm Federweg am Heck und Front bist du bereit für technische DHs, satte Drops und jede Line im Park. Die Ausstattung mit exklusivem Öhlins custom Stahlfeder-Öl-Dämpfer, RockShox Boxxer Team Federgabel, SRAM 1x10 Antrieb und extrem stabilen Roval Laufrädern vollendet das Enduro Expert Evo zu einem vielseitigen DH-Bike der besonderen Klasse.

- Der DH-orientierte Rahmen aus M5 Aluminium ist hoch belastbar, am vollaktiven und sensible FSR Hinterbau arbeiten 180mm Federweg; die 650b Geometrie schafft ein agiles Bike, das sich auch bergauf bewegen lässt; gedichtete Industrielager an allen Drehpunkten.
- Der custom Öhlins Stahlfeder-Öl-Dämpfer mit 180mm Federweg ist ein High-Performance-Dämpfer mit unabhängig von der Zugstufe einstellbarer High- und Lowspeed-Druckstufe; der einfach einzustellende Dämpfer bietet dir überragende Funktion und ist in dieser Form an keinem anderen Bike zu finden.
- Die RockShox Boxxer Team 650b mit 180mm Federweg und Charger Dämpfung ist für die schwierigsten DH-Strecken entwickelt worden; die hohe Steifigkeit und größen-spezifische Abstimmung machen die Boxxer zur idealen Gabel für das Enduro Evo.

2016 ENDURO EVO 650B			
SIZE	S	M	L
Stack (mm)	596	596	605
Reichweite (Reach) (mm)	405	430	460
Steuerrohrlänge (mm)	110	110	120
Steuerrohrwinkel (deg)	64.5	64.5	64.5
Tretlagerhöhe (mm)	352	352	352
Tretlagerabsenkung (mm)	2	2	2
Nachlauf (mm)	116	116	116
Gabellänge (mm)	570	570	570
Fork Rake/Offset (mm)	48	48	48
Mitte Tretlager - Mitte Vorderachse (mm)	742	767	801
Kettenstreben (mm) (mm)	423	423	423
Radstand (mm)	1164	1189	1224
Oberrohrlänge (horizontal) (mm)	545	570	602
Bike-Überstandshöhe (mm)	748	757	757
Sitzrohrlänge (mm)	391	414	454
Sitzrohrwinkel (deg)	76.8	76.8	76.8
Lenkerbreite (mm)	781	781	781
Vorbaulänge (mm)	45	45	45
Kurbellänge (mm)	165	165	165
Sattelstützen-Länge (mm)	367	367	367

SPECS	Technische Änderungen vorbehalten.
RAHMEN	M5 alloy, 650b geometry, tapered head tube, PF30 BB, 142mm dropouts, 180mm travel
DÄMPFER	Custom Öhlins, high/low speed compression adjust, rebound adjust, 8.75x2.5", S: 76x434lb, M: 84x479lb, L: 92x525lb
GABEL	RockShox Boxxer Team 650b, coil spring, S: Extra soft spring, M: Soft spring, L: Medium spring, XL: Firm spring, 180mm travel, charger damper, compression adjust, rebound adjust, alloy steerer, 48mm offset, Maxle Lite DH
STEUERSATZ	1-1/8" upper, 1-1/2" lower, threadless, Campy style, cartridge bearings
VORBAU	Specialized P.Series MTB, forged alloy, 4-bolt
LENKER	Specialized Demo, 7050 alloy, 8-degree backsweep, 6-degree upsweep, 25mm rise, 780mm, 31.8mm
LENKERGRIFFE	Specialized Sip Grip, light lock-on, half-waffle, S/M: regular thickness, L/XL: XL thickness
VORDERRADBREMSE	SRAM Guide RS DH, metallic pads, Code caliper, 200mm Centerline rotor
HINTERRADBREMSE	SRAM Guide RS DH, metallic pads, Code caliper, 180mm Centerline rotor
BREMSHEBEL	SRAM Guide RS DH, alloy lever, reach adjust, cartridge bearing lever pivot
SCHALTWERK	SRAM XO, 10-speed, short cage
SCHALTHEBEL	SRAM X9, 10-speed
KASSETTE	SRAM PG-1030, 10-speed, 11-36t
KETTE	SRAM PC-1031, 10-speed, w/ PowerLink, nickel finish
KURBELGARNITUR	SRAM Descendant, PF30, alloy arms, thin 32T ring, 170mm
INNENLAGER	SRAM, PF30, OS press-in bearings, sealed cartridge
PEDALE	Nylon, CEN std., w/ toe clips
FELGEN	Roval 650b, alloy, 24mm inner width, 32h
VORDERRADNABE	Specialized, Hi Lo disc, sealed cartridge bearings, 20mm thru-axle, 36h
HINTERRADNABE	Custom DT Swiss, Star Ratchet, XX1 driver body, 12mm thru-axle, 32h
SPEICHEN	DT Swiss Industry, stainless
VORDERREIFEN	Specialized Butcher DH, 60TPI, wire bead, 650bx2.5"
HINTERREIFEN	Specialized Slaughter DH, 60TPI, wire bead, 650bx2.3"
SCHLÄUCHE	Standard, Presta valve
SATTEL	Body Geometry Henge Comp, hollow Cr-Mo rails, 143mm
SATTELSTÜTZE	Thomson, alloy, straight, 12-degree clamp
SATTELSTÜTZKLEMME	Specialized, 7050 alloy, single bolt, 34.9mm

PART NO.	DESCRIPTION	COLOR	SIZE
93616-3202	ENDURO EXPERT EVO 650BCL	GRY/MX ORG/SLT	S
93616-3203			M
93616-3204			L