



CARB/TUR/WHT

Ambitionierten Frauen, die ein Rennrad mit Race-Charakter suchen, bietet das Amira SL4 Elite aufgrund des leichten und steifen FACT Karbonrahmens mit frauenspezifischer Geometrie spielerische Handling-Eigenschaften und beste Effizienz. Die hochwertigen Shimano 105 11-fach Komponenten und Fulcrum S5 Laufräder machen aus dem Amira ein renntaugliches Bike und in jedem Fall ein verdammt schnelles.

- Steifer und leichter FACT 9r Karbon-Rahmen mit frauenspezifischer Wettkampf-Geometrie, OSBB Tretlager für optimale Kraftübertragung und konischem Steuerrohr für präzise, direkte Lenkmanöver.
- Steife Monocoque-Gabel aus FACT Karbon mit konischem Schaft ermöglicht präzises Lenken.
- Fulcrum S5 Laufräder mit hoher Steifigkeit für direktes Fahrverhalten.

SPECS

SPECS	Technische Änderungen vorbehalten.
RAHMEN	Specialized FACT 9r carbon, FACT construction, Women's Competitive Geometry, women's layout w/ shaped/tapered 1-1/8" to 1-3/8" head tube, OSBB
GABEL	Specialized FACT carbon, full monocoque
STEUERSATZ	1-1/8" upper, 1-3/8" lower, integrated Cr-Mo cartridge bearings, 20mm cone spacer, w/ 20mm of spacers
VORBAU	Specialized Comp Multi, 3D forged alloy, 4-bolt, 12-degree rise
LENKER	Specialized Women's Comp, shallow drop, alloy, 123mm drop, 75mm reach
LENKERBAND	Specialized Roubaix
VORDERRADBREMSE	Shimano 105
HINTERRADBREMSE	Shimano 105
UMWERFER	Shimano 105, 11-speed
SCHALTWERK	Shimano 105, 11-speed
SCHALTHEBEL	Shimano 105 STI, 11-speed
KASSETTE	Shimano 105, 11-speed, 11-28t
KETTE	Shimano 105, 11-speed
KURBELGARNITUR	TURN Zayante by Praxis Works, BB30, 50/34T
PEDALE	Nylon, loose ball bearings, w/ reflectors
VORDERRAD	Fulcrum Racing S5
HINTERRAD	Fulcrum Racing S5
VORDERREIFEN	Specialized Turbo Pro, 127TPI, folding bead, BlackBelt protection, 700x23mm
HINTERREIFEN	Specialized Turbo Pro, 127TPI, folding bead, BlackBelt protection, 700x23mm
SCHLÄUCHE	Standard, Presta valve
SATTEL	Body Geometry Oura Comp, hollow Cr-Mo rails, 155mm
SATTELSTÜTZE	Specialized Comp Carbon, single bolt
SATTELSTÜTZKLEMME	Alloy, 31.6mm

PART NO.	DESCRIPTION	COLOR	SIZE
97216-4244	AMIRA SL4 ELITE CEN	CARB/TUR/WHT	44
97216-4248			48
97216-4251			51
97216-4254			54
97216-4256			56

2016 AMIRA					
SIZE	44.0	48.0	51.0	54.0	56.0
Stack (mm)	504	516	529	548	565
Reichweite (Reach) (mm)	365	371	378	378	380
Steuerrohrlänge (mm)	105	115	125	145	165
Steuerrohrwinkel (deg)	70.5	71.25	72	72	72
Tretlagerhöhe (mm)	268.5	268.5	268.5	268.5	270
Tretlagerabsenkung (mm)	73	73	73	73	72
Nachlauf (mm)	67	62	59	59	59
Gabellänge (mm)	369	369	369	369	369
Fork Rake/Offset (mm)	51	51	49	49	49
Mitte Tretlager - Mitte Vorderachse (mm)	576	580	582	588	596
Kettenstreben (mm) (mm)	405	405	405	405	408
Radstand (mm)	970	974	976	982	994
Oberrohrlänge (horizontal) (mm)	491	502	515	535	547
Bike-Überstandshöhe (mm)	692	718	735	758	777
Sitzrohrlänge (mm)	390	420	460	490	510
Sitzrohrwinkel (deg)	76	75.75	75.5	74	73.5
Lenkerbreite (mm)	360	380	400	400	400
Vorbaulänge (mm)	75	75	90	100	100
Kurbellänge (mm)	165	165	170	170	172.5
Sattelstützen-Länge (mm)	300	350	350	350	350