



NVY/CYAN/HYP



STRL GRV/FUS/DP TUR

Das Jett Sport fährt sich entspannt und leicht kontrollierbar, was besonders an den 29er Laufrädern, der frauenspezifischen XC Geometrie und der speziell abgestimmten SR Suntour Federgabel liegt. Abgerundet wird das stimmige Konzept durch hydraulische Tektro Auriga Scheibenbremsen mit Griffweiteneinstellung sowie die zuverlässige Shimano Schaltung.

- Der Rahmen aus A1 Premium Aluminium mit optimierter 29er XC-Geometrie für Frauen sorgt für ein leicht beherrschbares Bike mit hoher Agilität.
- Die SR Suntour XCM 29 Federgabel mit 80mm Federweg und exklusiv von Specialized entwickelter Multi-Circuit-Dämpfung schafft top Kontrolle und hohen Komfort im Gelände.
- Die hydraulischen Tektro Auriga Scheibenbremsen verzögern bei allen Witterungsbedingungen zuverlässig; einstellbare Hebelweite.

SPECS

	Technische Änderungen vorbehalten.
RAHMEN	Specialized A1 Premium Aluminum, Women's XC 29 Geometry, women's butted tube sets, forged post-mount 160mm dropouts, replaceable derailleur hanger, kickstand mount
GABEL	Custom SR Suntour XCM 29, custom Multi-Circuit Damping, custom coil spring weights, 80mm travel, preload adjust, 1-1/8" steerer, alloy lowers, Hi-Ten 30mm stanchions, disc mount
STEUERSATZ	1-1/8" upper/lower, ZeroStack 44, steel cups, loose ball bearings
VORBAU	Specialized, 3D forged alloy, 4-bolt, 6-degree rise
LENKER	Specialized Stout, flat bar, double-buttet 6061 alloy, 10-degree backsweep, 4-degree upsweep, 31.8mm
LENKERGRIFFE	Specialized Body Geometry XCT Women's, Kraton w/ gel, lock-on, closed end
VORDERRADBREMSE	Tektro Auriga, hydraulic disc, resin/metallic pads, 160mm rotor
HINTERRADBREMSE	Tektro Auriga, hydraulic disc, resin/metallic pads, 160mm rotor
BREMSHEBEL	Tektro Auriga, hydraulic, short reach adjust
UMWERFER	Shimano Altus, high mount, bottom swing, dual pull
SCHALTWERK	Shimano Acera Shadow, 9-speed
SCHALTHEBEL	Shimano Altus RapidFire Plus, SL type, optical display
KASSETTE	Sunrace, 9-speed, 11-34t
KETTE	KMC X9, 9-speed, w/ reusable MissingLink
KURBELGARNITUR	Specialized Stout, forged alloy, 9-speed, square taper spindle, 44/32/22T
INNENLAGER	Square taper, cartridge bearings
PEDALE	Plastic, 9/16", w/ reflectors
FELGEN	29", disc, alloy, double-wall, pin joint, 25mm inner width, 32h
VORDERRADNABE	Specialized Stout, Hi Lo disc, alloy, double-sealed, ground race, QR, 32h
HINTERRADNABE	Specialized Stout, Hi Lo disc, alloy, double-sealed, loose ball bearings, QR, 32h
SPEICHEN	Stainless, 14g
VORDERREIFEN	Specialized Ground Control Sport, 60TPI, wire bead, 29x2.1"
HINTERREIFEN	Specialized Fast Trak Sport, 30TPI, wire bead, Flak Jacket protection, 29x2.0"
SCHLÄUCHE	Standard, Schrader valve
SATTEL	Body Geometry Women's Riva Sport Plus, steel rails, 155mm
SATTELSTÜTZE	Alloy, 2-bolt, micro-adjust, 12.5mm offset, 27.2mm
SATTELSTÜTZKLEMME	Alloy, nylon/glass fiber washer, QR, 34.9mm

2016 JETT SPORT			
SIZE	S	M	L
Stack (mm)	612	623	633
Reichweite (Reach) (mm)	378	392	414
Steuerrohrlänge (mm)	100	110	120
Steuerrohrwinkel (deg)	70	70.5	70.5
Tretlagerhöhe (mm)	309	309	309
Tretlagerabsenkung (mm)	65	65	65
Nachlauf (mm)	87	83	83
Gabellänge (mm)	495	495	495
Fork Rake/Offset (mm)	46	46	46
Mitte Tretlager - Mitte Vorderachse (mm)	629	642	667
Kettenstreben (mm) (mm)	450	450	450
Radstand (mm)	1071	1084	1109
Oberrohrlänge (horizontal) (mm)	559	577	601
Bike-Überstandshöhe (mm)	373.5	373.5	373.5
Sitzrohrlänge (mm)	361	417	468
Sitzrohrwinkel (deg)	73.5	73.5	73.5
Lenkerbreite (mm)	660	660	660
Vorbaulänge (mm)	60	80	80
Kurbellänge (mm)	170	170	175
Sattelstützen-Länge (mm)	350	350	350

PART NO.	DESCRIPTION	COLOR	SIZE
91816-6002	JETT SPORT 29	NVY/CYAN/HYP	S
91816-6003			M
91816-6004			L
91816-6102	JETT SPORT 29	STRL GRV/FUS/DP TUR	S
91816-6103			M
91816-6104			L