



FLK SIL/BLK/BRT PNK

Unter den Frauen-MTBs ist unser Rumor 650b sicherlich so etwas wie eine Alleskönnerin. Es fährt sich gut rauf, geht flink über Trails und schafft viel Vertrauen und Sicherheit bergab. Die Women's Trail Geometrie mit kurzen Kettenstreben, niedrigem Tretlager und geringer Überstandshöhe gibt dir maximale Beherrschbarkeit und Sicherheit in technischen Passagen. Die 650b Laufräder unterstreichen die hohe Agilität, mit der das Rumor flink durch den Trail zirkelt. Dank 125mm Federweg schenkt dir das mit Rx Women's Trail Tune abgestimmte Fahrwerk genügend Reserven für grobes Terrain, Absätze und Sprünge. Die Komponenten-Wahl ist auf Zuverlässigkeit und solide Funktion ausgelegt. Auf zu neuen Trails und neuen Skills mit dem Rumor 650b!

- Der leichte M5 Aluminium-Rahmen mit 125mm Federweg und 650b Trail Geometrie für Frauen ergibt ein spielerisch kontrollierbares Trail-Bike mit viel Sicherheitsreserven durch geringe Überstandshöhe; der FSR-Hinterbau arbeitet jederzeit vollaktiv und unabhängig; die interne Zugführung berücksichtigt auch die Command Post-Verkabelung.
- Der custom X-Fusion RL Dämpfer mit 125mm Federweg verfügt mit dem Women's Rx Trail Tune über eine sensible, harmonische Abstimmung für geringere Fahrgewichte; somit erhält der FSR-Hinterbau maximalen Komfort und überragende Kontrolle über das Gelände.
- Die hydraulischen Tektro Gemini Scheibenbremsen lassen sich optimal dosieren und geben dir mit wenig Kraftaufwand volle Speed-Kontrolle.

2016 RUMOR 650B			
SIZE	S	M	L
Stack (mm)	587	592	602
Reichweite (Reach) (mm)	400	423	444
Steuerrohrlänge (mm)	94	100	110
Steuerrohrwinkel (deg)	68.5	68.5	68.5
Tretlagerhöhe (mm)	326.2	326.2	326.2
Tretlagerabsenkung (mm)	26	26	26
Nachlauf (mm)	94	94	94
Gabellänge (mm)	524	524	524
Fork Rake/Offset (mm)	42	42	42
Mitte Tretlager - Mitte Vorderachse (mm)	666	692	717
Kettenstreben (mm) (mm)	434	434	434
Radstand (mm)	1099	1124	1149
Oberrohrlänge (horizontal) (mm)	544	571	597
Bike-Überstandshöhe (mm)	1047.4	1055.3	1056.4
Sitzrohrlänge (mm)	387	430	445
Sitzrohrwinkel (deg)	76.2	76	75.8
Lenkerbreite (mm)	700	700	700
Vorbaulänge (mm)	60	75	90
Kurbellänge (mm)	165	170	175
Sattelstützen-Länge (mm)	350	350	390

SPECS	Technische Änderungen vorbehalten.
RAHMEN	M5 aluminum, Women's Trail 650b Geometry, women's fully-butted tube sets, tapered head tube, PF30 BB, DMD mounts, internal cable routing, internal Command Posting routing, 142mm dropouts, SRAM FD adapter, 125mm travel
DÄMPFER	Custom X-Fusion O2 Pro RL, air sleeve, rebound adjust, lockout, 205x53mm
GABEL	RockShox Recon Silver 650b, Solo Air spring, 130mm travel, TurnKey compression adjust, 46mm offset, 15mm Maxle Lite thru-axle
STEUERSATZ	1-1/8" upper, 1-1/2" lower, Campy style, integrated sealed cartridge bearings
VORBAU	Specialized Trail, forged alloy, 4-bolt, 8-degree rise
LENKER	Specialized Stout, flat bar, double-butted 6061 alloy, 10-degree backsweep, 4-degree upsweep, 31.8mm
LENKERGRIFFE	Specialized Sip Grip, light lock-on, half-waffle, regular thickness
VORDERRADBREMSE	Tektro Gemini, hydraulic disc, resin pads, I-spec compatible
HINTERRADBREMSE	Tektro Gemini, hydraulic disc, resin pads, I-spec compatible
BREMSEBEL	Tektro Gemini, hydraulic, short reach adjust
UMWERFER	SRAM X5, 2x10
SCHALTWERK	Shimano Deore Shadow, 9-speed, SGS cage, top mount
SCHALTHEBEL	Shimano Alivio, 9-speed
KASSETTE	Shimano, 9-speed, 11-34t
KETTE	KMC X9, 9-speed
KURBELGARNITUR	Custom SRAM S-1250, 7050 alloy arms, 10-speed double, PF30, 34/22T, 104/64mm BCD spider
INNENLAGER	SRAM, PF30, OS press-in bearings, sealed cartridge
PEDALE	Nylon, 9/16", loose ball bearings, w/ reflectors
FELGEN	Alex XD, 650b, 24/28h
VORDERRADNABE	Specialized, Hi Lo disc, sealed cartridge bearings, 15mm thru-axle, 24h
HINTERRADNABE	Specialized, Hi Lo disc, 4x sealed cartridge bearings, 12mm thru-axle, 28h
SPEICHEN	Stainless, 14g, black
VORDERREIFEN	Specialized Purgatory Control, 60TPI, 2Bliss Ready, folding bead, 650bx2.3"
HINTERREIFEN	Specialized Ground Control, 60TPI, 2Bliss Ready, folding bead, 650bx2.3"
SCHLÄUCHE	Standard, Presta valve
SATTEL	Body Geometry Women's Myth Sport, steel rails, 155mm
SATTELSTÜTZE	Alloy, 2-bolt, 12.5mm offset, 30.9mm, anti-corrosion hardware
SATTELSTÜTZKLEMME	Alloy, QR, 34.9mm

PART NO.	DESCRIPTION	COLOR	SIZE
95316-7402	RUMOR 650B	FLK SIL/BLK/BRT PNK	S
95316-7403			M
95316-7404			L