



RYL BLU/CYAN

Das "P" in "P.Bikes" steht nicht etwa für "Pretty, denn hier findest du keinen Schnickschnack, keine Verkünstelungen. P.Bikes sind ultra-stabil, versehen mit top Material und Geometrien, die sich im Street-, Park-, und Dirt-Einsatz bewähren. Auf dem P.20 mit 20.5" langem Oberrohr und kurzem Hinterbau wirst du sofort merken, dass das Stahl-Chassis und die hochwertigen Komponenten zum gnadenlosen Shredden gemacht sind. Ach ja, das "P" steht für "Progressive".

- Rahmen aus Hi-Ten-Stahl mit MID BB Tretlager; die Geometrie mit 20.5" langem Oberrohr eignet sich für Dirt, Park und Street; 5mm dicke, super robuste Ausfallenden.
- Hoch belastbare P.Series Hi-Ten Stahl-Gabel mit konifzierten Gabelscheiden.
- 3-teilige, innen hohle "P.Crank" Kurbel aus Cr-Mo-Stahl verkraften härteste Belastungen.

2016 P 20	
SIZE	20.5
Stack (mm)	366
Reichweite (Reach) (mm)	432
Steuerrohrlänge (mm)	110
Steuerrohrwinkel (deg)	74.5
Tretlagerhöhe (mm)	290
Tretlagerabsenkung (mm)	-36
Nachlauf (mm)	38
Gabellänge (mm)	314
Fork Rake/Offset (mm)	31
Mitte Tretlager - Mitte Vorderachse (mm)	577
Kettenstreben (mm) (mm)	342
Radstand (mm)	916
Oberrohrlänge (horizontal) (mm)	551
Bike-Überstandshöhe (mm)	568
Sitzrohrlänge (mm)	235
Sitzrohrwinkel (deg)	72
Lenkerbreite (mm)	735
Vorbaulänge (mm)	50
Kurbellänge (mm)	170
Sattelstützen-Länge (mm)	200

SPECS	Technische Änderungen vorbehalten.
RAHMEN	Hi-Ten plain gauge steel, 20.5" top tube, MID BB shell, seatstay-mounted U-brake bosses, 5mm thick dropouts for 14mm axle
GABEL	Hi-Ten steel, tapered blades, 1-1/8" threadless, 5mm Cr-Mo dropouts for 3/8" axle
STEUERSATZ	1-1/8", threadless, Campy style, integrated full cartridge bearings, 8mm cone spacer
VORBAU	Alloy, top load, 50mm, 22.2mm clamp
LENKER	Specialized P.Series BMX, steel, 11-degree backsweep, 2-degree upsweep, 217mm rise, 735mm, 22.2mm
LENKERGRIFFE	P.Grip BMX, w/ flange, Kraton, end plugs, 150mm
VORDERRADBREMSE	Tektro, U-brake
HINTERRADBREMSE	Tektro, U-brake
BREMSHEBEL	Tektro, U-brake
KETTE	KMC Z510H, single speed, 1/2"x1/8", anti-drop inner links
KURBELGARNITUR	P.Crank, 3 pc., Cr-Mo tubular arms, 8-spline, 170mm
KETTENBLÄTTER	25T
INNENLAGER	MID BB, 19mm 8-spline spindle, sealed cartridge bearings
PEDALE	Specialized P.Series, plastic body w/ molded pins, Cr-Mo spindle, loose ball bearings, 9/16"
FELGEN	P.20, alloy, single wall, center void, 32mm inner width, 36h
VORDERRADNABE	P.Series BMX, alloy, loose ball bearings, solid axle, 36h
HINTERRADNABE	P.Series BMX, alloy, sealed cartridge bearings, hollow axle, 36h
SPEICHEN	Stainless, 14g, black
VORDERREIFEN	Specialized Compound Street, 2.3"
HINTERREIFEN	Specialized Compound Street, 2.3"
SCHLÄUCHE	Standard, Schrader valve
SATTEL	P.Seat SL, 1 pc. w/ co-molded alloy 25.4mm seatpost
SATTELSTÜTZE	Alloy, 0mm offset, 25.4mm, integrated w/ saddle

PART NO.	DESCRIPTION	COLOR	SIZE
91916-4020	P.20	RYL BLU/CYAN	20.5" TT