



BLK/CYAN/WHT

Unser Ariel Elite Disc gehört zu jenen Bikes, die den Namen Alleskönner verdienen. Mit einer speziellen Fitness-Geometrie für Frauen eignet es sich hervorragend zum Pendeln, Tourenfahren oder den sportiven Ausritt über Feld- und Waldwege. Der fahrstabile Rahmen aus A1 Premium Aluminium des Ariel Elite Disc wird komplettiert mit hochwertigen Shimano Deore Komponenten, einer speziell abgestimmten SR Suntour Federgabel mit "Multi-Circuit"- Dämpfung und hydraulischen Shimano Scheibenbremsen.

- Der Rahmen aus A1 Premium Aluminium überzeugt durch bestes Handling und hohe Fahrstabilität; die Women's Fitness-Geometrie sorgt für eine entspannte Sitzposition, in der du länger und angenehmer fährst; optionale Montage von Schutzblechen und Gepäckträger.
- Die SR Suntour i-NEX Federgabel mit hydraulischem Lockout und exklusiver Multi-Circuit Dämpfung bietet 63 mm effektiv arbeitenden Federweg für viel Komfort und Kontrolle.
- Die hydraulischen Shimano-Scheibenbremsen stehen für kontrolliertes Bremsen bei jedem Wetter.

SPECS	Technische Änderungen vorbehalten.
RAHMEN	Specialized A1 Premium Aluminum, Women's Fitness Geometry, women's double-butted tube sets, forged dropouts, disc mount, fender/rack mounts
GABEL	Custom SR Suntour i-NEX, custom Multi-Circuit Damping, women's custom coil spring weights, 63mm travel, hydraulic lockout, preload adjust, 1-1/8" steerer, alloy lowers, Hi-Ten 28mm stanchions, post disc mount
STEUERSATZ	FSA, semi-integrated bearings
VORBAU	Specialized, 3D forged alloy, 4-bolt, 6-degree rise
LENKER	Specialized, flat bar, double-butted 6061 alloy, 10-degree backsweep, 31.8mm
LENKERGRIFFE	Specialized Body Geometry XCT Women's, lock-on, closed end
VORDERRADBREMSE	Shimano BR-M395, hydraulic disc, resin pads, 160mm rotor
HINTERRADBREMSE	Shimano BR-M395, hydraulic disc, resin pads, 160mm rotor
BREMSEBEL	Shimano, hydraulic
UMWERFER	Shimano Deore, top swing, dual pull
SCHALTWERK	Shimano Deore Shadow, 10-speed, SGS cage, direct mount
SCHALTHEBEL	Shimano Deore, 10-speed
KASSETTE	Shimano, 10-speed, 11-36t
KETTE	KMC X10, 10-speed, w/ reusable MissingLink
KURBELGARNITUR	Specialized Stout, forged alloy, 10-speed, 44/32T, w/ chainguard
INNENLAGER	Square taper, cartridge bearings
PEDALE	Alloy, w/ reflectors
FELGEN	Alloy, double-wall, disc
VORDERRADNABE	Specialized Stout, Hi Lo disc, alloy, double-sealed, ground race, QR, 32h
HINTERRADNABE	Specialized Stout, Hi Lo disc, alloy, double-sealed, loose ball bearings, QR, 32h
SPEICHEN	Stainless, 14g
VORDERREIFEN	Specialized Trigger Sport, 60TPI, BlackBelt protection, 700x38mm
HINTERREIFEN	Specialized Trigger Sport, 60TPI, BlackBelt protection, 700x38mm
SCHLÄUCHE	Standard, Schrader valve
SATTEL	Body Geometry Women's Riva Sport Plus, steel rails, 155mm
SATTELSTÜTZE	Alloy, 2-bolt, micro-adjust, 12.5mm offset, 27.2mm
SATTELSTÜTZKLEMME	Alloy, 31.8mm

2016 ARIEL A1 DISC					
SIZE	XS	S	M	L	XL
Stack (mm)	588	607	621	635	659
Reichweite (Reach) (mm)	380	386	395	406	414
Steuerrohrlänge (mm)	85	105	120	135	160
Steuerrohrwinkel (deg)	70	70	70	70	70
Tretlagerhöhe (mm)	297	297	297	297	297
Tretlagerabsenkung (mm)	60	60	60	60	60
Nachlauf (mm)	89	89	89	89	89
Gabellänge (mm)	490	490	490	490	490
Fork Rake/Offset (mm)	38	38	38	38	38
Mitte Tretlager - Mitte Vorderachse (mm)	616	629	643	658	675
Kettenstreben (mm) (mm)	445	445	445	445	445
Radstand (mm)	1054	1067	1081	1097	1113
Oberrohrlänge (horizontal) (mm)	560	572	585	600	615
Bike-Überstandshöhe (mm)	699.3	738	771	803.7	849.4
Sitzrohrlänge (mm)	345	395	440	485	550
Sitzrohrwinkel (deg)	73	73	73	73	73
Lenkerbreite (mm)	640	640	660	660	660
Vorbaulänge (mm)	60	70	70	90	90
Kurbellänge (mm)	165	165	170	170	175
Sattelstützen-Länge (mm)	350	350	350	350	350

PART NO.	DESCRIPTION	COLOR	SIZE
92215-4001	ARIEL ELITE DISC	BLK/CYAN/WHT	XS
92215-4002			SM
92215-4003			MD
92215-4004			LG
92215-4005			XL