



MET BLK/SIL/PRL CRL/TUR

Bringe deine Fitness mit dem Ariel Sport Disc aufs nächste Level, und wähle dabei selbst zwischen Asphalt und leichtem Gelände. Mit einer speziellen Fitness-Geometrie für Frauen eignet es sich hervorragend für gemütliche wie sportive Ausritte. Der Rahmen aus A1 Premium Aluminium wird ergänzt durch eine komfortable SR Suntour Federgabel mit exklusiver Multi-Circuit Dämpfung und hydraulischen Tektro- Scheibenbremsen.

- Der Rahmen aus A1 Premium Aluminium überzeugt durch bestes Handling und hohe Fahrstabilität; die Women's Fitness-Geometrie sorgt für eine entspannte Sitzposition, in der du länger und angenehmer fährst; optionale Montage von Schutzblechen und Gepäckträger.
- Die SR Suntour i-NEX Federgabel mit hydraulischem Lockout und exklusiver Multi-Circuit Dämpfung bietet 63mm effektiv arbeitenden Ferweg für viel Komfort und Kontrolle.
- Die hydraulischen Tektro Auriga Scheibenbremsen verzögern kontrolliert bei jedem Wetter und lassen sich in der Griffweite anpassen.

SPECS	Technische Änderungen vorbehalten.
RAHMEN	Specialized A1 Premium Aluminum, Women's Fitness Geometry, women's double-butted tube sets, forged dropouts, disc mount, fender/rack mounts
GABEL	Custom SR Suntour i-NEX, custom Multi-Circuit Damping, women's custom coil spring weights, 63mm travel, hydraulic lockout, preload adjust, 1-1/8" steerer, alloy lowers, Hi-Ten 28mm stanchions, post disc mount
STEUERSATZ	FSA, semi-integrated bearings
VORBAU	Specialized, 3D forged alloy, 4-bolt, 6-degree rise
LENKER	Specialized, double-butted 6061 alloy, 9-degree backsweep, 5-degree upsweep, 15mm rise, 31.8mm
LENKERGRIFFE	Specialized Body Geometry XCT Women's, lock-on, closed end
VORDERRADBREMSE	Tektro Auriga, hydraulic disc, resin pads, 160mm rotor
HINTERRADBREMSE	Tektro Auriga, hydraulic disc, resin pads, 160mm rotor
BREMSEBEL	Tektro, hydraulic
UMWERFER	Shimano Altus, top swing, dual pull
SCHALTWERK	Shimano Alivio, 9-speed
SCHALTHEBEL	Shimano SL-M370 RapidFire Plus, 9-speed
KASSETTE	Shimano, 9-speed, 11-34t
KETTE	KMC X9, 9-speed, w/ reusable MissingLink
KURBELGARNITUR	Specialized Stout, forged alloy, 48/36/26T, w/ chainguard
INNENLAGER	Square taper, cartridge bearings
PEDALE	Plastic, w/ reflectors
FELGEN	Alloy, double-wall, disc
VORDERRADNABE	Specialized Stout, Hi Lo disc, alloy, double-sealed, ground race, QR, 32h
HINTERRADNABE	Specialized Stout, Hi Lo disc, alloy, double-sealed, loose ball bearings, QR, 32h
SPEICHEN	Stainless, 14g
VORDERREIFEN	Specialized Trigger Sport, 60TPI, BlackBelt protection, 700x38mm
HINTERREIFEN	Specialized Trigger Sport, 60TPI, BlackBelt protection, 700x38mm
SCHLÄUCHE	Standard, Schrader valve
SATTEL	Body Geometry Women's Riva Sport Plus, steel rails, 155mm
SATTELSTÜTZE	Alloy, 2-bolt, micro-adjust, 12.5mm offset, 27.2mm
SATTELSTÜTZKLEMME	Alloy, 31.8mm

2016 ARIEL A1 DISC					
SIZE	XS	S	M	L	XL
Stack (mm)	588	607	621	635	659
Reichweite (Reach) (mm)	380	386	395	406	414
Steuerrohrlänge (mm)	85	105	120	135	160
Steuerrohrwinkel (deg)	70	70	70	70	70
Tretlagerhöhe (mm)	297	297	297	297	297
Tretlagerabsenkung (mm)	60	60	60	60	60
Nachlauf (mm)	89	89	89	89	89
Gabellänge (mm)	490	490	490	490	490
Fork Rake/Offset (mm)	38	38	38	38	38
Mitte Tretlager - Mitte Vorderachse (mm)	616	629	643	658	675
Kettenstreben (mm) (mm)	445	445	445	445	445
Radstand (mm)	1054	1067	1081	1097	1113
Oberrohrlänge (horizontal) (mm)	560	572	585	600	615
Bike-Überstandshöhe (mm)	699.3	738	771	803.7	849.4
Sitzrohrlänge (mm)	345	395	440	485	550
Sitzrohrwinkel (deg)	73	73	73	73	73
Lenkerbreite (mm)	640	640	660	660	660
Vorbaulänge (mm)	60	70	70	90	90
Kurbellänge (mm)	165	165	170	170	175
Sattelstützen-Länge (mm)	350	350	350	350	350

PART NO.	DESCRIPTION	COLOR	SIZE
92216-6001	ARIEL SPORT DISC	MET BLK/SIL/PRL CRL/TUR	XS
92216-6002			S
92216-6003			M
92216-6004			L
92216-6005			XL