



CHAR/BLK/LT PRL TUR/PRL TUR

Unser Ariel Disc gehört zu jenen Bikes, die den Namen Alleskönner verdienen. Mit einer speziellen Fitness-Geometrie für Frauen eignet es sich hervorragend zum Pendeln, Tourenfahren oder die sportive Ausfahrt über Feld- und Waldwege. Das Ariel verfügt über einen hochwertigen Rahmen aus A1 Premium Aluminium, an dem eine SR Suntour Federgabel für viel Komfort sorgt. Für sicheres Bremsen sorgen die mechanischen Scheibenbremsen aus dem Haus Tektro.

- Der Rahmen aus A1 Premium Aluminium überzeugt durch bestes Handling und hohe Fahrstabilität; die Women's Fitness-Geometrie sorgt für eine entspannte Sitzposition, in der du länger und angenehmer fährst; optionale Montage von Schutzblechen und Gepäckträger.
- Die SR Suntour i-NEX Federgabel mit hydraulischem Lockout und exklusiver Multi-Circuit Dämpfung bietet 63mm effektiv arbeitenden Ferweg für viel Komfort und Kontrolle.
- Die mechanischen Tektro Aries Scheibenbremsen verzögern kontrolliert bei jedem Wetter.

SPECS	Technische Änderungen vorbehalten.
RAHMEN	Specialized A1 Premium Aluminum, Women's Fitness Geometry, women's double-butted tube sets, forged dropouts, disc mount, fender/rack mounts
GABEL	Custom SR Suntour i-NEX, custom Multi-Circuit Damping, women's custom coil spring weights, 63mm travel, hydraulic lockout, preload adjust, 1-1/8" steerer, alloy lowers, Hi-Ten 28mm stanchions, post disc mount
STEUERSATZ	FSA, semi-integrated bearings
VORBAU	Forged alloy, 4-bolt, 10-degree rise
LENKER	Specialized, 6061 alloy, 8-degree backsweep, 5-degree upsweep, 25mm rise, 25.4mm
LENKERGRIFFE	Specialized Body Geometry XCT Women's, lock-on, closed end
VORDERRADBREMSE	Tektro Aries, mechanical disc, organic pads
HINTERRADBREMSE	Tektro Aries, mechanical disc, organic pads
BREMSEBEL	Tektro, mechanical disc
UMWERFER	Shimano FD-M191, top swing, dual pull
SCHALTWERK	Shimano Altus, 8-speed
SCHALTHEBEL	Shimano SL-M310, RapidFire Plus, 8-speed
KASSETTE	Shimano, 8-speed, 12-32t
KETTE	KMC X8, 8-speed, w/ reusable MissingLink
KURBELGARNITUR	Specialized Stout, forged alloy, 48/36/26T, w/ chainguard
INNENLAGER	Square taper, cartridge bearings
PEDALE	Plastic, w/ reflectors
FELGEN	Alloy, double-wall, disc
VORDERRADNABE	Specialized Stout, Hi Lo disc, alloy, double-sealed, ground race, QR, 32h
HINTERRADNABE	Specialized Stout, Hi Lo disc, alloy, double-sealed, loose ball bearings, QR, 32h
SPEICHEN	Stainless, 14g
VORDERREIFEN	Specialized Trigger Sport, 60TPI, BlackBelt protection, 700x38mm
HINTERREIFEN	Specialized Trigger Sport, 60TPI, BlackBelt protection, 700x38mm
SCHLÄUCHE	Standard, Schrader valve
SATTEL	Body Geometry Women's Riva Sport Plus, steel rails, 155mm
SATTELSTÜTZE	Alloy, 2-bolt, micro-adjust, 12.5mm offset, 27.2mm
SATTELSTÜTZKLEMME	Alloy, 31.8mm

2016 ARIEL A1 DISC					
SIZE	XS	S	M	L	XL
Stack (mm)	588	607	621	635	659
Reichweite (Reach) (mm)	380	386	395	406	414
Steuerrohrlänge (mm)	85	105	120	135	160
Steuerrohrwinkel (deg)	70	70	70	70	70
Tretlagerhöhe (mm)	297	297	297	297	297
Tretlagerabsenkung (mm)	60	60	60	60	60
Nachlauf (mm)	89	89	89	89	89
Gabellänge (mm)	490	490	490	490	490
Fork Rake/Offset (mm)	38	38	38	38	38
Mitte Tretlager - Mitte Vorderachse (mm)	616	629	643	658	675
Kettenstreben (mm) (mm)	445	445	445	445	445
Radstand (mm)	1054	1067	1081	1097	1113
Oberrohrlänge (horizontal) (mm)	560	572	585	600	615
Bike-Überstandshöhe (mm)	699.3	738	771	803.7	849.4
Sitzrohrlänge (mm)	345	395	440	485	550
Sitzrohrwinkel (deg)	73	73	73	73	73
Lenkerbreite (mm)	640	640	660	660	660
Vorbaulänge (mm)	60	70	70	90	90
Kurbellänge (mm)	165	165	170	170	175
Sattelstützen-Länge (mm)	350	350	350	350	350

PART NO.	DESCRIPTION	COLOR	SIZE
92216-7101	ARIEL DISC	CHAR/BLK/LT PRL TUR/PRL TUR	XS
92216-7102			S
92216-7103			M
92216-7104			L
92216-7105			XL