



BLK/CHAR/ORG



DRTY WHT/RKT RED/CYAN

Mit dem Crosstrail geht es entspannt auf die Feierabendrunde oder die Tour am Wochenende. Der leichte Rahmen aus A1 Premium Aluminium bietet direkten Vortrieb, direktes Handling und eine ausgewogene Sitzposition. Die 38mm breiten Reifen rollen schnell auf festen Untergründen und bieten die nötige Sicherheit im leichten Gelände. Die Federgabel dämpft dank Multi-Circuit Dämpfung effektiv und kontrolliert, mittels hydraulischem Lockout ist sie schnell anpassbar auf den Straßeneinsatz.

- Der leichte Rahmen aus A1 Premium Aluminium wurde unter Einbezug unseres Body Geometry Fit Teams entwickelt, was ihm seine ausgewogene, entspannte Sitzposition beschert; zudem punktet er mit hoher Fahrstabilität, geringem Gewicht sowie praktischer Vielseitigkeit durch Vorrichtungen für Schutzblech- und Gepäckträgermontage.
- Die SR Suntour NEX Federgabel mit hydraulischem Lockout und Multi-Circuit Dämpfung bietet 60 mm effektiv arbeitenden Federweg für viel Komfort und Kontrolle.
- Die XCT Lock-Griffe und der Targa Comp Sattel wurden unter Body Geometry Aspekten entwickelt, um die Durchblutung in den Händen und im Sitzbereich aufrecht zu erhalten; in der Praxis bedeutet das spürbar mehr Komfort und Wohlbefinden, selbst auf längeren Strecken.

2016 CROSSOVER M4					
SIZE	XS	S	M	L	XL
Stack (mm)	565	584	598	612	635
Reichweite (Reach) (mm)	387	394	402	413	421
Steuerrohrlänge (mm)	85	105	120	135	160
Steuerrohrwinkel (deg)	70	70	70	70	70
Tretlagerhöhe (mm)	297	297	297	297	297
Tretlagerabsenkung (mm)	60	60	60	60	60
Nachlauf (mm)	89	89	89	89	89
Gabellänge (mm)	465	465	465	465	465
Fork Rake/Offset (mm)	38	38	38	38	38
Mitte Tretlager - Mitte Vorderachse (mm)	614	627	641	657	673
Kettenstreben (mm) (mm)	445	445	445	445	445
Radstand (mm)	1052	1066	1079	1095	1112
Oberrohrlänge (horizontal) (mm)	560	572	585	600	615
Bike-Überstandshöhe (mm)	736.8	772.1	357	357	357
Sitzrohrlänge (mm)	345	395	440	485	550
Sitzrohrwinkel (deg)	73	73	73	73	73
Lenkerbreite (mm)	680	680	680	680	680
Vorbaulänge (mm)	60	75	90	90	100
Kurbellänge (mm)	170	170	175	175	175
Sattelstützen-Länge (mm)	350	350	350	350	350

SPECS	Technische Änderungen vorbehalten.
RAHMEN	Specialized A1 Premium Aluminum, Fitness Geometry, fully-manipulated butted tubing, fender/rack mounts
GABEL	Custom SR Suntour NEX, custom Multi-Circuit Damping, custom coil spring weights, 60mm travel, hydraulic lockout, alloy lowers, Hi-Ten stanchions, V-brake mount
STEUERSATZ	FSA, semi-integrated bearings
VORBAU	Forged alloy, 4-bolt, 10-degree rise
LENKER	Specialized, 6061 alloy, 8-degree backsweep, 5-degree upsweep, 25mm rise, 25.4mm
LENKERGRIFFE	Specialized Body Geometry XCT, lock-on
VORDERRADBREMSE	V-brake, alloy, linear pull
HINTERRADBREMSE	V-brake, alloy, linear pull
BREMSHEBEL	Alloy
UMWERFER	Shimano FD-M191, top swing, dual pull
SCHALTWERK	Shimano Altus, 8-speed
SCHALTHEBEL	Shimano SL-M310, RapidFire Plus, 8-speed
KASSETTE	Shimano, 8-speed, 12-32t
KETTE	KMC X8, 8-speed, w/ reusable MissingLink
KURBELGARNITUR	Specialized Stout, forged alloy, 48/38/28T, w/ chainguard
INNENLAGER	Square taper, cartridge bearings
PEDALE	Nylon, w/ reflectors
FELGEN	Alloy, double-wall
VORDERRADNABE	Double-sealed, QR, 32h
HINTERRADNABE	Double-sealed, QR, 32h
SPEICHEN	Stainless, 14g
VORDERREIFEN	Specialized Trigger Sport, 60TPI, BlackBelt protection, 700x38mm
HINTERREIFEN	Specialized Trigger Sport, 60TPI, BlackBelt protection, 700x38mm
SCHLÄUCHE	Standard, Schrader valve
SATTEL	Body Geometry Targa Sport, steel rails, SWAT compatible mounts, 155mm
SATTELSTÜTZE	Alloy, 2-bolt, micro-adjust, 12.5mm offset, 27.2mm
SATTELSTÜTZKLEMME	Alloy, 31.8mm

PART NO.	DESCRIPTION	COLOR	SIZE
92415-7002	CROSSTRAIL	BLK/CHAR/ORG	S
92415-7003			M
92415-7004			L
92415-7005			XL
92415-7006			XXL
92416-7102	CROSSTRAIL	DRTY WHT/RKT RED/CYAN	S
92416-7103			M
92416-7104			L
92416-7105			XL
92416-7106			XXL