



CARB/RKT RED/SIL

Das SIRRUS Pro Carbon ist Speed pur! Mit seiner entspannten Fitness-Geometrie kombiniert es den Leichtlauf eines Rennrades mit dem Komfort eines geraden Lenkers. Der effiziente Karbon-Rahmen garantiert direkten Vortrieb und ein agiles Handling. Mit der Shimano Ultegra 2x11 Schaltung wechselst du blitzschnell und super einfach die Gänge; die Übersetzung ist auch für bergige Strecken voll tauglich. Die hydraulischen Shimano-Scheibenbremsen lassen sich fein dosieren und verzögern kräftig, wenn du es brauchst. Wie wäre es mit einer Dosis SIRRUS-Speed?

- Leichter Rahmen aus FACT 9r Karbon mit entspannter Fitness-Geometrie und Zertz-Dämpfungseinsätzen für geschmeidiges Fahrverhalten; die Monocoque-Gabel aus FACT Karbon unterstützt das direkte Lenkverhalten, Zertz-Einsätze filtern Vibrationen; Plug&Play Aufnahme zur einfachen Montage von Schutzblechen.
- Der steife, leichte Axis 4.0 Disk Laufradsatz wird bestückt mit schnell laufenden Specialized Roubaix Pro Reifen, die mit 28mm Breite viel Komfort ermöglichen. Der BlackBelt Pannenschutz steht ganz im Zeichen deiner Sicherheit.
- Der Rahmen verfügt über eine ausgewogene Fitness-Geometrie, in der du sowohl komfortabel als auch effizient unterwegs bist; der Specialized Body Geometry Phenom Comp Sattel ist unter medizinischen Gesichtspunkten entwickelt, um die Durchblutung in sensiblen Arterien zu gewährleisten.

2016 SIRRUS CARBON				
SIZE	S	M	L	XL
Stack (mm)	574	591	616	650
Reichweite (Reach) (mm)	395	403	410	420
Steuerrohrlänge (mm)	150	165	190	225
Steuerrohrwinkel (deg)	71	71.5	72	72
Tretlagerhöhe (mm)	275	275	275	275
Tretlagerabsenkung (mm)	70	70	70	70
Nachlauf (mm)	65	62	58	58
Gabellänge (mm)	398	398	398	398
Fork Rake/Offset (mm)	51	51	51	51
Mitte Tretlager - Mitte Vorderachse (mm)	627	635	645	666
Kettenstreben (mm) (mm)	435	435	435	435
Radstand (mm)	1052	1060	1070	1091
Oberrohrlänge (horizontal) (mm)	568	578	598	619
Bike-Überstandshöhe (mm)	752.2	784.6	821.9	860.3
Sitzrohrlänge (mm)	440	485	530	570
Sitzrohrwinkel (deg)	73.3	73.5	73	73
Lenkerbreite (mm)	580	600	600	620
Vorbaulänge (mm)	90	90	105	105
Kurbellänge (mm)	170	172.5	172.5	175
Sattelstützen-Länge (mm)	300	300	350	350

SPECS	Technische Änderungen vorbehalten.
RAHMEN	Specialized FACT 9r carbon, Fitness Geometry, Zertz, internal cable routing, tapered/integrated headset, post disc mount, Plug + Play fender mount
GABEL	Specialized FACT carbon, full monocoque, Zertz, post disc mounts, Plug + Play fender mounts
STEUERSATZ	FSA, Campy style, integrated cartridge bearings
VORBAU	Specialized Flow Set, integrated, 3D forged alloy, 4-bolt, 12-degree rise
LENKER	Specialized, flat bar, double-buttet 6061 alloy, 10-degree backsweep, 4-degree upsweep, 31.8mm
LENKERBAND	Specialized Body Geometry Targa, lock-on, w/ integrated bar ends
VORDERRADBREMSE	Shimano BR-M615, hydraulic disc, resin pads w/ fins, 160mm Ice-Tech rotor
HINTERRADBREMSE	Shimano BR-M615, hydraulic disc, resin pads w/ fins, 140mm Ice-Tech rotor
BREMSHEBEL	Shimano, hydraulic
UMWERFER	Shimano Ultegra, 11-speed, braze-on
SCHALTWERK	Shimano Ultegra, 11-speed
SCHALTHEBEL	Shimano SL-RS700 RapidFire Plus, 11-speed
KASSETTE	Shimano, 11-speed, 11-32t
KETTE	KMC X11SL DLC, 11-speed, w/ reusable MissingLink
KURBELGARNITUR	FSA SL-K Light, hollow carbon arms, MegaEVO BB, 50/34T, 110mm BCD spider
INNENLAGER	FSA MegaEvo, threaded
PEDALE	Nylon body, alloy cage, low profile bearing system
VORDERRAD	AXIS 4.0 Disc
HINTERRAD	AXIS 4.0 Disc
VORDERREIFEN	Specialized Roubaix Pro Reflect, 120TPI, folding bead, BlackBelt protection, Endurant casing, 700x25/28mm
HINTERREIFEN	Specialized Roubaix Pro Reflect, 120TPI, folding bead, BlackBelt protection, Endurant casing, 700x25/28mm
SCHLÄUCHE	Standard, Presta valve
SATTEL	Body Geometry Phenom Expert, hollow Ti rails, 143mm
SATTELSTÜTZE	Specialized CG-R, FACT carbon, single bolt, reflective, 27.2mm
SATTELSTÜTZKLEMME	Alloy, 31.6mm

PART NO.	DESCRIPTION	COLOR	SIZE
90916-1002	SIRRUS PRO CARBON	CARB/RKT RED/SIL	S
90916-1003			M
90916-1004			L
90916-1005			XL