

SOURCE COMP DISC STEP THROUGH



BLU

Das Source Comp Disc Step ist ein wahres Multi-Talent für's Pendeln, Tourenfahren oder den Alltags-Einsatz. Dafür sorgen ein fahrstabiler, leichter Aluminium-Rahmen mit halbhochem Durchstieg, Gepäckträger, Schutzbleche und eine helle Supernova Beleuchtung. Die hochwertige Shimano 2x10 Kettenschaltung bietet eine universelle Übersetzung, die hydraulischen Shimano Scheibenbremsen funktionieren bei jedem Wetter zuverlässig und berechenbar.

- Specialized Espoir Sport Reflect 700x30c Reifen punkten mit geschmeidigem Leichtlauf und erhöhter Sichtbarkeit dank Reflexstreifen.
- Hochwertige Lichtanlage mit Shimano Nabendynamo in Verbindung mit Supernova E3 Pure 3 Frontlampe und E3 Rücklicht; Standlichtfunktion
- Der Custom Racktime Light-it Gepäckträger mit spezieller Schutzblech-Befestigung ist ideal für das Anbringen von Packtaschen; maximale Zuladung: 20kg; die leichten Specialized Aluminium-Schutzbleche vereinen gute Schutzfunktion und ansprechende Optik.

2016 SOURCE E5 ST			
SIZE	S	M	L
Stack (mm)	552	574	589
Reichweite (Reach) (mm)	383	386	386
Steuerrohrlänge (mm)	130	150	165
Steuerrohrwinkel (deg)	70	71	71
Tretlagerhöhe (mm)	275	275	275
Tretlagerabsenkung (mm)	70	70	70
Nachlauf (mm)	71	65	65
Gabellänge (mm)	398	398	398
Fork Rake/Offset (mm)	51	51	51
Mitte Tretlager - Mitte Vorderachse (mm)	616	617	622
Kettenstreben (mm) (mm)	439	439	439
Radstand (mm)	1045	1047	1052
Oberrohrlänge (horizontal) (mm)	536	551	566
Bike-Überstandshöhe (mm)	604.8	609.8	620.6
Sitzrohrlänge (mm)	395	440	475
Sitzrohrwinkel (deg)	74.5	74	73
Lenkerbreite (mm)	640	640	640
Vorbaulänge (mm)	75	80	90
Kurbellänge (mm)	170	172.5	172.5
Sattelstützen-Länge (mm)	350	350	350

SPECS	Technische Änderungen vorbehalten.
RAHMEN	Specialized E5 Premium Aluminum, fully-manipulated tubing w/ smooth welds, compact design, integrated headset, internal cable routing, fender/rack mounts, kickstand mount
GABEL	Specialized FACT carbon, alloy steerer/crown, Zertz, post disc mount, Plug + Play fender mount
STEUERSATZ	1-1/8" sealed Cr-Mo bearings integrated w/ headset, 15mm alloy cone spacer
VORBAU	Specialized, 3D forged alloy, 4-bolt, 7-degree rise
LENKER	Specialized, flat bar, double-buttet 6061 alloy, 9-degree backsweep, 31.8mm
LENKERGRIFFE	Specialized Body Geometry Contour Women's, w/ integrated bar end
VORDERRADBREMSE	Shimano BR-M506, hydraulic disc, dual piston, I-spec compatible, 160mm Centerlock rotor
HINTERRADBREMSE	Shimano BR-M506, hydraulic disc, dual piston, I-spec compatible, 160mm Centerlock rotor
BREMSHEBEL	Shimano BL-M506, I-spec compatible
UMWERFER	SRAM X7, 2x10
SCHALTWERK	Shimano XT Shadow, 10-speed, SGS cage
SCHALTHEBEL	Shimano Deore RapidFire Plus, 10-speed, I-spec
KASSETTE	Shimano, 10-speed, 11-36t
KETTE	KMC X10, 10-speed, w/ reusable MissingLink
KURBELGARNITUR	FSA Omega, 7075 alloy, 48/34T
KETTENBLÄTTER	48/34
INNENLAGER	FSA, external bearings
PEDALE	Nylon body, alloy cage, low profile bearing system
FELGEN	Alloy, double-wall, disc, pin joint, 32h
VORDERRADNABE	Shimano DH-3D72, Centerlock, 3W, 32h
HINTERRADNABE	Specialized, Hi Lo disc, alloy, loose ball bearings, QR, 32h
SPEICHEN	Stainless, 14g, black
VORDERREIFEN	Specialized Espoir Sport, double BlackBelt protection, reflective, 700x30mm
HINTERREIFEN	Specialized Espoir Sport, double BlackBelt protection, reflective, 700x30mm
SCHLÄUCHE	Standard, Presta valve
SATTEL	Body Geometry Women's Riva Sport, steel rails, 155mm
SATTELSTÜTZE	Alloy, 2-bolt, micro-adjust, 12.5mm offset, 27.2mm
SATTELSTÜTZKLEMME	Alloy, 31.8mm
SCHEINWERFER	Supernova E3 PURE 3, w/ standlight
RÜCKLICHT	Supernova E3
STÄNDER	Specialized, center mount
GEPÄCKTRÄGER	Custom Racktime Light-it, w/ Snap-in
SCHUTZBLECHE	Specialized, aluminum, w/ anodized struts
KLINGEL	Mini Bell, aluminum, w/ pivoted lever

PART NO.	DESCRIPTION	COLOR	SIZE
91015-5102	SOURCE COMP DISC STEP THROUGH	BLU	S
91015-5103			M
91015-5104			L