



MX ORG/WHT/BLK

Das "P" in "P.Bikes" steht nicht etwa für "Pretty, denn hier findest du keinen Schnickschnack, keine Verkünstelungen. P.Bikes sind ultra-stabil, versehen mit top Material und Geometrien, die sich im Street-, Park-, und Dirt-Einsatz bewähren. Mit dem P.20 Grom bringen alle jungen Nachwuchs-Shredder ihre Skills mit viel Spaß auf das nächste Level. Ach ja, das "P" steht für "Progressive".

- Rahmen aus Hi-Ten-Stahl: hart im Nehmen, gute Dämpfungseigenschaften für die ersten Tricks; 21" langes Oberrohr für viel Bewegungsfreiheit; 5mm dicke, super robuste Ausfallenden.
- Hoch belastbare P.Series Hi-Ten Stahl-Gabel mit konifizierten Gabelscheidern.
- 3-teilige, innen hohle "P.Crank" Kurbel aus Cr-Mo-Stahl verkraften härteste Belastungen.

SPECS

Technische Änderungen vorbehalten.

RAHMEN	Hi-Ten plain gauge steel, 21" top tube, 1-1/8" head tube, seatstay-mounted U-brake bosses, 5mm dropouts for 14mm axle
GABEL	Hi-Ten steel, 1-1/8" threadless steerer, 3/8" axle dropouts
STEUERSATZ	Ahead, 1/8" sealed cartridge bearings
VORBAU	Alloy, 40mm clamp
LENKER	Specialized P.Series BMX, steel, 11-degree backsweep, 2-degree upsweep, 168mm rise, 640mm, 22.2mm
LENKERGRIFFE	Specialized, Kraton, closed end, 105mm
VORDERRADBREMSE	Tektro, U-brake
HINTERRADBREMSE	Tektro, U-brake
BREMSEHEBEL	Tektro, U-brake
KASSETTE	Odyssey, 13t
KETTE	KMC Z510, single speed, anti-drop, 1/2"x1/8"
KURBELGARNITUR	P.Crank, 3 pc. BMX style, 8-spline, 152mm
KETTENBLÄTTER	30T, 1/2"x1/8"
INNENLAGER	8-spline
PEDALE	Nylon, 9/16"
FELGEN	Alloy, single wall, 36h
VORDERRADNABE	Alloy, 3/8" axle, loose ball bearings, dual lock nuts, 17mm contact side, nutted, 32h
HINTERRADNABE	Alloy, 14mm axle, 36h
SPEICHEN	Stainless, 14g
VORDERREIFEN	Specialized Rhythm Lite, 2.0"
HINTERREIFEN	Specialized Rhythm Lite, 2.0"
SCHLÄUCHE	Standard, Schrader valve
SATTEL	P.Seat SL, padded, 1 pc. w/ co-molded alloy 25.4mm seatpost

2016 P GROM	
SIZE	20.5
Stack (mm)	379
Reichweite (Reach) (mm)	385
Steuerrohrlänge (mm)	110
Steuerrohrwinkel (deg)	74.5
Tretlagerhöhe (mm)	290
Tretlagerabsenkung (mm)	-36
Nachlauf (mm)	43
Gabellänge (mm)	318
Fork Rake/Offset (mm)	26
Mitte Tretlager - Mitte Vorderachse (mm)	528
Kettenstreben (mm) (mm)	347
Radstand (mm)	872
Oberrohrlänge (horizontal) (mm)	508
Bike-Überstandshöhe (mm)	558
Sitzrohrlänge (mm)	235
Sitzrohrwinkel (deg)	72
Lenkerbreite (mm)	0
Vorbaulänge (mm)	0
Kurbellänge (mm)	0
Sattelstützen-Länge (mm)	0

PART NO.	DESCRIPTION	COLOR	SIZE
B1916-3518	P.20 GROM	MX ORG/WHT/BLK	20" TT