

SOURCE SPORT DISC STEP THROUGH



CHAR/BLK

Das Source Sport Disc Step ist ein wahres Multi-Talent für's Pendeln, Tourenfahren oder den Alltags-Einsatz. Dafür sorgen ein fahrstabiler, leichter Aluminium-Rahmen mit halbhochem Durchstieg, Gepäckträger und Schutzbleche. Die hochwertige Shimano 3x9 Kettenschaltung bietet für jede Situation den richtigen Gang, die hydraulischen Tektro Scheibenbremsen funktionieren bei jedem Wetter zuverlässig und berechenbar.

- Rahmen aus A1 Premium Aluminium mit hoher Fahrstabilität und ausgewogener Geometrie für eine entspannte Sitzposition. Halbhoher Durchstieg für komfortables Auf- und Absteigen.
- Der frauenspezifische Body Geometry Riva Sport Sattel wurde mit dem Ziel optimaler Durchblutungsleistung und effektiver Druckminderung entwickelt und schafft so auf langen wie kurzen Strecken angenehmen Komfort.
- Der Custom Racktime Light-it Gepäckträger mit spezieller Schutzblech-Befestigung ist ideal für das Anbringen von Päcktaschen; maximale Zuladung: 20kg; die leichten Specialized Aluminium-Schutzbleche vereinen gute Schutzfunktion und ansprechende Optik.

2016 SOURCE A1 ST			
SIZE	S	M	L
Stack (mm)	584	600	626
Reichweite (Reach) (mm)	394	402	409
Steuerrohrlänge (mm)	150	165	190
Steuerrohrwinkel (deg)	71	71.5	72
Tretlagerhöhe (mm)	281	281	281
Tretlagerabsenkung (mm)	70	70	70
Nachlauf (mm)	67	64	60
Gabellänge (mm)	410	410	410
Fork Rake/Offset (mm)	51	51	51
Mitte Tretlager - Mitte Vorderachse (mm)	629	637	647
Kettenstreben (mm) (mm)	445	445	445
Radstand (mm)	1065	1073	1082
Oberrohrlänge (horizontal) (mm)	570	580	600
Bike-Überstandshöhe (mm)	750	786	821
Sitzrohrlänge (mm)	440	485	530
Sitzrohrwinkel (deg)	73.25	73.5	73
Lenkerbreite (mm)	640	640	640
Vorbaulänge (mm)	75	80	90
Kurbellänge (mm)	170	175	175
Sattelstützen-Länge (mm)	350	350	350

SPECS	Technische Änderungen vorbehalten.
RAHMEN	Specialized A1 Premium Aluminum, step through, fully-manipulated tubing, integrated headset, disc mount, fender/rack mounts, kickstand mount, Rollerbrake mounting points
GABEL	Alloy legs/crown, Cr-Mo steerer, internal light cable routing, fender/rack mounts
STEUERSATZ	1-1/8" sealed Cr-Mo bearings integrated w/ headset, 15mm alloy cone spacer
VORBAU	Specialized, 3D forged alloy, 4-bolt, 7-degree rise
LENKER	Specialized, flat bar, double-budded 6061 alloy, 9-degree backsweep, 31.8mm
LENKERGRIFFE	Specialized Body Geometry Contour Women's, lock-on, closed end
VORDERRADBREMSE	Tektro Auriga, hydraulic disc, resin/metallic pads, 160mm rotor
HINTERRADBREMSE	Tektro Auriga, hydraulic disc, resin/metallic pads, 160mm rotor
BREMSEBEL	Tektro Auriga, hydraulic, reach adjust
UMWERFER	Shimano FD-T3000, top swing, dual pull
SCHALTWERK	Shimano Acera Shadow, 9-speed
SCHALTHEBEL	Shimano Acera RapidFire Plus, SL type, 9-speed, w/ optical display
KASSETTE	Shimano CS-HG300, 9-speed, 11-34t
KETTE	KMC X9, 9-speed, w/ reusable MissingLink
KURBELGARNITUR	Specialized Stout, forged alloy, 48/36/26T, w/ chainguard
KETTENBLÄTTER	48/38/28T
INNENLAGER	Square taper, cartridge bearings
PEDALE	Nylon body, alloy cage, low profile bearing system
FELGEN	Alloy, double-wall, disc
VORDERRADNABE	Specialized Stout, Hi Lo disc, alloy, double-sealed, ground race, QR, 32h
HINTERRADNABE	Specialized Stout, Hi Lo disc, alloy, double-sealed, loose ball bearings, QR, 32h
SPEICHEN	Stainless, 14g, black
VORDERREIFEN	Specialized Nimbus, Flak Jacket protection, reflective, 700x35mm
HINTERREIFEN	Specialized Nimbus, Flak Jacket protection, reflective, 700x35mm
SCHLÄUCHE	Standard, Presta valve
SATTEL	Body Geometry Women's Riva Sport, steel rails, 155mm
SATTELSTÜTZE	Alloy, 2-bolt, micro-adjust, 12.5mm offset, 27.2mm
SATTELSTÜTZKLEMME	Alloy, 31.8mm
STÄNDER	Specialized, center mount
GEPÄCKTRÄGER	Custom Racktime Light-it, w/ Snap-in
SCHUTZBLECHE	Specialized, aluminum, w/ anodized struts
KLINGEL	Mini Bell, aluminum, w/ pivoted lever

PART NO.	DESCRIPTION	COLOR	SIZE
91016-6102	SOURCE SPORT DISC STEP THROUGH	CHAR/BLK	S
91016-6103			M
91016-6104			L